

Unrivalled surface protection and manoeuvrability

Part No.	Description	Standard Application	Max Load (kgs)	Frame Dimensions (mm)	Toe Dimensions (mm)	Weight (kg)
HTSC-S-201	Standard body, double wheel	Appliance/General Purpose	220	1370 x 400 (570 incl. wheels)	400 x 212	17.5
HTSC-S-301	Standard body, triple wheels			1370 x 400 (610 incl. wheels)	400 x 212	18.5
HTSC-S-212	Tall body, double wheels			1540 x 455 (630 incl. wheels)	455 x 212	19.5
HTSC-S-312	Tall body, triple wheels			1540 x 455 (670 incl. wheels)	455 x 212	20.5



Avoids contact with stair nosings

Small wheel base enables load to be fully supported on a step

Moulded wheel guards protect doors and walls from gouging



HTSC-S-201

HTSC-S-312

Applications

The Rotatruck stair climbing hand truck allows users to transport heavy or awkward loads up and down stairs with greater safety and confidence. Suitable for use in a number of environments including transport and logistics, furniture and appliance removals, office, retail or general warehouse.

Benefits

- Direct tracking capability and improved steering control.
- 360° movement providing easy rotational and direct sideways manoeuvrability without marking or scrubbing floors unlike pneumatic wheels.
- Easy repositioning of the load laterally across the width of a stair to safely negotiate stair landings and other confined spaces.
- 30cm wide wheel base enables a safe resting position on a single step, greatly reducing the risk of a runaway load.
- Easy clearance of stair nosing avoiding contact and damage of stairs.
- Ribbed rail buffers give multiple points of contact with the load for increased stability and protection.
- Moulded wheel guards prevent gouging or damaging of walls and doors.
- Rotatruck brand load safety strap standard for increased load safety.