COLOCK"



EasierFasterSafer

Get an immediate ROI with simultaneous improvement in both productivity and safety.





Rotatruck® vs. Handtruck

The smaller Rotacaster wheel at the front gives the Rotatruck greater leverage than traditional 2-wheelers, making it easier to pull back, park, lever and balance loads.

More leverage, less effort

The Rotatruck's compact, multidirectional wheel base fully supports loads without operator input. No need to park or pull back loads as frequently.

Just push, don't carry

The fixed orientation of the Rotacaster wheel allows you to step and lever loads instead of turning and reversing (over obstacles), with 78% less effort and 63% faster.

Lever, don't lift

32% less pull-back effort

55% less general handling effort



Easier pull-back effort & no need to park at waypoints.



Parking and pulling back loads at waypoints increases strain on musculoskeletal structure.

Hands Free Balance™

Leverage Plus™

Okg load to carry



The Rotatruck carries the load, not the operator.



Constant operator input to maintain load balance exerting strain and effort.

Magic Step Up™

78% less lifting effort **63% faster**negotiating kerbs



Up kerbs or over obstructions without reversing.



Maximum effort required to reverse and pull load up a kerb.

Dual Nose Rotatruck™

The Dual Nose Rotatruck™ for general material handling and delivery is the easiest, quickest and safest way to handle large and heavy items. Its ergonomic design minimises repetitive pull back, bending and user effort.



Dual Nose Rotatruck with wide frame kit

PRODUCT CODES:

Standard Noses: 11-23-AT/2601 XL bottom nose: 11-23-AT/2702 2 XL noses: 11-23-AT/2703

- · Load Capacity: 220kg
- · Load capacity folding nose: 100kg
- · Weight: 23kg

COMPONENTS

- · Aluminium straight frame
- · 2x 125mm R3 Rotacaster™ wheels
- · 250mm foam filled rear wheels
- · Optional ratchet strap

Self-Supporting Wheel Base

Self-supporting multi-directional Rotatrucks are based on a highly manoeuvrable four wheeled base that increases productivity.



Foldable Nose

An **additional folding Nose** reduces bending and lifting required and carries loads up to 100kg.
Optional with XL noses (20x12").



Optional Wide Frame Kit

Optional aluminium wide frame kit to **increase the frame width** from 305mm to 445mm.



Puncture Proof Rear Wheel

The puncture proof **Microcell foam rear wheels** navigate with ease through rough surfaces.



Optional Ratchet Strap

The **Ratchet Strap** ensures that the load does not become dislodged when being transported and is adjustable.

